

1

CLAIMS

2 What is claimed is:

3

4 1. A light assembly for a vehicle comprising, in combination:

5 a light; and

6 an attachment bracket adapted to secure the light to the vehicle;

7 wherein as the vehicle leans the light pivots directly in response to the pull of

8 gravity in a direction opposite the lean of the vehicle.

9

10 2. The light assembly of claim 1 wherein the attachment bracket has a pair of

11 side flanges forming a C-shape, and the light is attached to the attachment bracket

12 between the side flanges.

13

14 3. The light assembly of claim 1 further comprising a bolt rotatable with respect

15 to the vehicle, which extends through the attachment bracket, wherein the

16 attachment bracket is rotatable with the bolt.

17

18 4. The light assembly of claim 3 wherein the bolt is hollow, and wiring is

19 positioned in the bolt adapted to electrically connect the light to a source of

20 electricity.

21

PATENT

1 5. The light assembly of claim 3 wherein the bolt is threaded and a nut and
2 washer engages the bolt to secure the attachment bracket to the bolt so as to resist
3 dislocation of the bolt from the attachment bracket.

4

5 6. The light assembly of claim 3 further comprising a bearing assembly
6 positioned around the bolt so that the bolt is rotatably captivated with respect to the
7 vehicle to permit relative rotation of the bolt with respect to the bearing assembly.

8

9 7. The light assembly of claim 1 wherein the vehicle is a motorcycle.

10

11 8. The light assembly of claim 1 wherein the light is a vertical cutoff light.

12

13 9. The light assembly of claim 1 further comprising a connector connecting the
14 light to the vehicle.

15

16 10. The light assembly of claim 9 wherein the connector is elbow shaped and has
17 an opening sized to receive a bearing assembly, and the bearing assembly is rigidly
18 connected to the connector.

19

20 11. The light assembly of claim 1 further comprising left and right lights, each light
21 positioned on a corresponding front portion of the vehicle.

22

PATENT

1 12. The light assembly of claim 1 wherein the light is pivotable about a horizontal
2 axis with respect to the vehicle.